

## Safety Hand Lamp LED, EX-4DCL, ATEX

- Ambient temperature: -20°C to +40°C
- Beam type: Spot
- Beam distance: 50 metres
- Light duration: Up to 20 hours
- Power: 6V, 1W
- Power source: 4 x LR20 (D) alkaline cells (not included)

- Protection rating: IP66
- Product weight: 850 g (without battery and shoulder strap)
- Dimensions: 134 x 140 x 188 mm

Certified for ATEX Zones 1, 2, 21, and 22  
II 2G Ex ib op is IIC T4 Gb  
II 2D Ex ib IIIC T135°C Db IP66



Code: 74954

## Head Light LED, EX-2980, ATEX

- Ambient temperature: -20°C to +40°C
- Beam type: Spot/flood
- Beam distance: 58 metres
- Light duration: 5,3 hours (high) / 16 hours (low) / 11,5 hours (flood) / 7,5 hours (strobe light)
- Power: 4,5V, 1,8W
- Power source: 3 X LR03 (AAA) alkaline batteries (not included)

- Protection rating: IP67
- Production weight: 116 g (without batteries)
- Dimensions: 87 x 61 x 49 mm

Certified for ATEX Zones 0, 1, 2, 20, 21, and 22.  
I M1 Ex ia I Ma  
II 2G Ex ia op is IIC T4 Gb  
II 2D Ex ia IIIC T135°C Db IP66



Code: 74956

## Safety Rescue Torch Right Angle LED, EX-2280, ATEX

- Ambient temperature: -20°C to +40°C
- Beam type: Spot
- Beam Distance: 120 metres
- Light duration: 5,5 hours (high) / 9 hours (medium) / 22 hours (low) / 16 hours (strobe light) / 14 hours (S.O.S)
- Power: 6V, 3W
- Power source: 4 x LR6 (AA) alkaline batteries (not included)

- Protection rating: IP66
- Product weight: 230 g (without batteries)
- Dimensions: 60 x 103 x 180 mm

Certified for ATEX Zones 1, 2, 21, and 22.  
II 2G Ex ib op is IIC T4 Gb  
II 2D Ex ib IIIC T130°C Db



Code: 74955

## Safety Flashlight LED, EX-6180, ATEX

- Ambient temperature: -20°C to +40°C
- Beam type: Spot
- Beam distance: 80 metres
- Light duration: Up to 15 hours
- Power: 3V, 1,7W
- Power source: 2 x LR20 (D) primary alkaline cells (not included)
- Protection rating: IP67

- Product weight: 176 g (without batteries)
- Dimensions: Ø 65, L: 200 mm

Certified for ATEX Zones 0, 1, 2, 20, 21, and 22.  
I M1 Ex ia I Ma  
II 2G Ex ia op is IIC T4 Ga  
II 2D Ex ia op is IIIC T135°C Da



Code: 74957

## Safety Wand for Flashlight EX-6180, B-60

- Combined with the Safety Flashlight LED, EX-6180, ATEX - code: 74957 (sold separately)
- Durable, shockproof, with high impact resistance

- Can be used for various applications, such as marine signaling, aircraft safety, car safety, directing traffic, crowd control, and construction zones
- Dimensions: 166,7 x 48 mm



Code: 74958

Suitable for use in potentially hazardous environments, where atmospheres may contain flammable or explosive substances, as well as oil rigs, applications in the maritime industry, firefighting operations etc.